

AUTOMATIC DISH-WASHING LIQUID

Safety Data Sheet



Issued: July 2021

Section 1 - Identification of the Material and Supplier

Chemical nature:	Water solution of potassium hydroxide, sodium hydroxide and other ingredients.
Trade Name:	Automatic Dish-Washing Liquid
Product Use:	Machine dish-washing liquid.
Creation Date:	July 2021
This version issued:	This SDS issued July 2021 shall remain valid for 5 years unless a new SDS is issued in the meantime. Please contact Cleaning Trade Sales & Service to ensure you have the latest version of this product's SDS.

SUPPLIER DETAILS Poisons Information Centre: Phone 13 11 26 from anywhere in Australia

Company: Cleaning Trade Sales & Service
Address: 1/68 Reservoir Road, Modbury SA 5092, Australia
Telephone: 08 8395 9409
Web: www.ctss.net.au
Email: admin@ctss.net.au

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xn, Harmful. N, Dangerous to the environment. C, Corrosive. Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: S6

ADG Classification: Class 8: Corrosive Substances.

UN Number: 1719, CAUSTIC ALKALI LIQUID, N.O.S. (Potassium hydroxide, Sodium hydroxide).



GHS Signal word: DANGER

Acute Toxicity Oral – Category 4

Skin Corrosion – Category 1

Eye Corrosion – Category 1

HAZARD STATEMENT:

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

PREVENTION

P102: Keep out of reach of children.

P260: Do not breathe fumes, mists, vapours or spray.

P264: Wash contacted areas thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P301+P312: IF SWALLOWED: Call a POISON CENTRE phone Australia 131 126 or doctor if you feel unwell.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTRE phone Australia 131 126 or doctor/physician.

P330: Rinse mouth.

AUTOMATIC DISH-WASHING LIQUID

Safety Data Sheet

P363: Wash contaminated clothing before reuse.

STORAGE

P405: Store locked up.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Clear, red liquid.

Odour: No odour.

Major Health Hazards: Causes severe burns, harmful if swallowed.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Potassium hydroxide	1310-58-3	10-<30	2	Peak
Sodium carbonate	497-19-8	<5	not set	not set
Sodium metasilicate	6834-92-0	<5	not set	not set
EDTA Tetrasodium	64-02-8	10-<30	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Skin Contact: Seek urgent medical attention. Flush contaminated area with lukewarm, gently flowing water for at least 60 minutes, by the clock. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this MSDS and take their advice). Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Strongly basic ingredients tend to penetrate the skin and so need longer rinsing than other substances.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 60 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this MSDS and take their advice). Take care not to rinse contaminated water into the unaffected eye or onto face. Call a Poisons Information Centre or a doctor urgently. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting; rinse mouth thoroughly with water and contact a Poisons Information Centre. Urgent hospital treatment is likely to be needed. Give activated charcoal if instructed.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is little risk of an explosion from this product if commercial quantities are involved in a fire.

Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire. This will only occur after heating to dryness.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Not combustible. Use extinguishing media suited to burning materials. Water fog or fine spray is the preferred medium for large fires. Aim to dilute the material with large quantities of water. If practical, contain diluted material and prevent from entering drains and water courses.

AUTOMATIC DISH-WASHING LIQUID

Safety Data Sheet

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is little danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is liquid-tight chemical protective clothing and breathing apparatus.

Flash point:	Does not burn.
Upper Flammability Limit:	Does not burn.
Lower Flammability Limit:	Does not burn.
Autoignition temperature:	Not applicable - does not burn.
Flammability Class:	Does not burn.

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, Viton, Nitrile, butyl rubber, Barricade, neoprene, Teflon, polyethylene, PE/EVAL, Saranex, Responder. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary. Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Because of the corrosiveness of this product, special personal care should be taken in any cleanup operation. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. Contaminated area may be neutralised by washing with weak or dilute acid. Vinegar, citrus juice and most soft drinks may be suitable. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area. Check containers periodically for corrosion and leaks. Containers should be kept closed in order to minimise contamination. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m³)	STEL (mg/m³)
Potassium hydroxide	2	Peak
Sodium carbonate	not set	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that vapours and mists are minimised.

Eye Protection: Your eyes must be completely protected from this product by splash resistant goggles with face shield. All surrounding skin areas must be covered. Emergency eye wash facilities must also be available in an area close to where this product is being used.

AUTOMATIC DISH-WASHING LIQUID

Safety Data Sheet

Skin Protection: Because of the dangerous nature of this product, make sure that all skin areas are completely covered by impermeable gloves, overalls, hair covering, apron and face shield. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, Viton, nitrile, butyl rubber, Barricade, neoprene, Teflon, polyethylene, PE/EVAL, Saranex, Responder. **Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Clear, red liquid.
Odour:	No odour.
Boiling Point:	Above 100°C at 100kPa.
Freezing/Melting Point:	Below 0°C.
Volatiles:	Water component.
Vapour Pressure:	2.37 kPa at 20°C (water vapour pressure).
Vapour Density:	As for water.
Specific Gravity:	1
Water Solubility:	Completely soluble in water.
pH:	13
Odour Threshold:	No data.
Evaporation Rate:	As for water.
Coeff Oil/water Distribution:	No data
Autoignition temp:	Not applicable - does not burn.

Section 10 - Stability and Reactivity

Reactivity: Most strong alkalis and bases react with inorganic and organic acids to form salts. They can also react with some metals liberating hydrogen gas. These reactions may be rapid and sometimes liberate much heat. They can also decompose many organic materials such as esters, in a reaction called hydrolysis.

Conditions to Avoid: Keep containers tightly closed. Handle and open containers carefully.

Incompatibilities: acids, zinc, tin, aluminium and their alloys, any material reactive with extremely alkaline liquids.

Fire Decomposition: Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire. This will only occur after heating to dryness. Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Potassium and sodium compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Information on toxicological effects:

Acute toxicity	May be harmful if swallowed. Acute Oral LD50: Rat = approx. 1834 mg/kg (calculated, based on data from components)
Skin corrosion/irritation	Corrosion
Serious eye damage/irritation	Serious eye damage
Respiratory or skin sensitisation	No known significant effects or hazards.
Germ cell mutagenicity	No known significant effects or hazards.
Carcinogenicity	No known significant effects or hazards.
Reproductive toxicity	No known significant effects or hazards.
Specific target organ toxicity (STOT)- single exposure	No known significant effects or hazards.
Specific target organ toxicity (STOT)- repeated exposure	No known significant effects or hazards.
Aspiration hazard	No known significant effects or hazards.

AUTOMATIC DISH-WASHING LIQUID

Safety Data Sheet

Classification of Hazardous Ingredients

Ingredient:

Potassium hydroxide
Sodium metasilicate
EDTA Tetrasodium

Health effects:

Skin corrosion and serious eye damage. Harmful if swallowed.
Skin corrosion and serious eye damage.
Serious eye damage. Harmful if swallowed.

Potential Health Effects

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. However product may be irritating.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: This product is very corrosive to the skin. Capable of causing severe burns with deep ulceration, and can penetrate to deeper layers of skin resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure. Burns may not be immediately painful; the onset of pain may be minutes to hours.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is very corrosive to eyes. It will quickly cause severe pain, and corrosion of the eye and surrounding facial tissues. Unless exposure is immediately treated, permanent blindness and facial scarring will occur.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Available data shows that this product is harmful, but symptoms are not available. However, this product is very corrosive to the gastrointestinal tract. Capable of causing severe burns with deep ulceration, and can penetrate to deeper layers of skin resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

Section 12 - Ecological Information

This product is harmful to aquatic organisms. Until diluted or neutralised it will kill all aquatic organisms it contacts due to extreme pH.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to separate the contamination in some way. Only if neither of these options is suitable, we suggest that you contact a specialist disposal company to arrange disposal, but we recommend that it be neutralised in a controlled manner before disposal.

Section 14 - Transport Information

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1719, CAUSTIC ALKALI LIQUID, N.O.S. (Potassium hydroxide, Sodium hydroxide).

Hazchem Code: 2R

Special Provisions: 274

Limited quantities: ADG 7 specifies a Limited Quantity value of 1 L for this class of product.

Dangerous Goods Class: Class 8: Corrosive Substances.

AUTOMATIC DISH-WASHING LIQUID

Safety Data Sheet

Packing Group: II

Packing Instruction: P001, IBC02

Class 8 Corrosive Substances shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances where the Toxic Substances are cyanides and the Corrosives are acids), 7 (Radioactive Substances), Foodstuffs and foodstuff empties. They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Poisonous Gases), 3 (Flammable liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 6 (Toxic Substances except where the Toxic Substances are cyanides and the Corrosives are acids) and 9 (Miscellaneous Dangerous Goods).

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

The following ingredients: Potassium hydroxide, Sodium hydroxide, Sodium metasilicate (as alkaline salt), are mentioned in the SUSMP.

Section 16 - Other Information

This document has been produced in accordance with the requirements of the Globally Harmonised System of Classification and Labeling.

Please read all labels carefully before using product.

End of SDS.